

Milnor – Two-Stage Press

Benefits

Removes more water

This model delivers fastest production, with highest water removal.

Saves time

Holds two batches at once--one in pre-press stage, another in main press.

Membrane pressure extracts evenly

Soft, pliable membrane adapts to the shape of the batch, allowing even pressure throughout--no need to supplement it with air pressure.

Microprocessor is flexible, easy to use

Proven microprocessor control provides 16 programmable extraction sequences. Forty character alphanumeric display gives status.

Better extraction saves dryer fuel

Pressure is 31 bar (36 bar also available in 130 lb./60 kg size).

Faster repairs mean less downtime

Superior product support through local, highly-skilled dealers.

Specifications

Rated Capacity	130.0 lb.	59 kg
Dimensions and Weights		
Approx. Net Weight	19,170.0 lb.	8,695 kg
Press Specifications		
Pressure pump motor standard flow	7.5 HP	5.6 kW
Pressure pump motor high flow	10.0 HP	7.5 kW
Volume pump motor	10.0 HP	7.5 kW
Sled drive motor	2 x 0.8 HP	2 x 0.6 kW
Maximum pressure	450 psi	31 bar
Nominal cake diameter	40.00 in.	1,016 mm
Bed discharge height	16.56 in.	421 mm