

Milnor – Pass-through Dryer For Large Systems

Benefits

Speed boosts productivity.

Fast drying results from strong airflow and high heat input.

Simplified lint collection.

Milnor's lint filter system eliminates the need to manually clean the dryer's lint filter. This system strips the dryer's internal lint filter clean after each dry cycle.

Controller provides efficiency.

Microprocessor control allows field-programming for dry formulas. Dryer controls can also be linked to a Miltdata computer system for central programming, system monitoring and production reporting.

Built for long life. - Powder-coat painted for thorough protection.

Fixed Tilt.

This places the heaviest goods, which are the wettest, nearest the heat entry and also offers faster dry times and easier unloading.

Efficient, space saving design.

Our mirror-mount design feature allows two 64058 dryers to install side-by-side. The motors and controls can mount on either side of unit, optimizing floor space.

Patented long-life Energy-Saver seal.

Milnor maintains proper air flow. It keeps the hot air flowing through the goods, without letting it escape around the outside of the basket.

Specifications

Rated Capacity	200.0 - 320.0 lb.	91 - 145 kg
Dimensions and Weights		
Approx. Net Weight	5,360.0 lb.	2,431 kg
Overall Width	85.00 - 86.50 in.	2,159 - 2,197 mm
Overall Depth	103.20 in.	2,621 mm
Overall Height	146.75 - 168.31 in.	3,727 - 4,275 mm
Cylinder Size		
Cylinder Diameter	64.00 in.	1,626 mm
Cylinder Depth	58.00 in.	1,473 mm
Cylinder Volume	108.00 cu. Ft.	3,058 L
Motors		
Basket Drive Motor	3.0 HP	2.2 kW
Blower Motor	25.0 HP	18.6 kW